



## Control Panel 742 Isolation Transformers

- Designed for use in control circuits and general purpose applications.
- Finger proof shrouded screw connectors, with large funnelled aperture for ease of wiring.
- High quality steel laminated core, interleaved for minimum iron losses.
- Traditionally constructed, core windings totally varnished and stoved.
- Designed to conform generally to BS1711 (1978), BS3535 Part 1 1990, and EN60 742.
- Selective ranges available on each transformer, with European style fixing brackets for easy access and quick installation.



Reference	Rating	Dimensions (mm)					Weight (kg)	Enclosure
		Internals			Fixing			
		Width (W)	Depth (D)	Height (H)	Width (FW)	Depth (FD)		
GST50	50VA	75	66	85	63	43	1.1	<a href="#">P1</a>
GST100	100VA	98	72	100	80	55	2.0	<a href="#">P1</a>
GST150	150VA	98	78	100	80	61	2.5	<a href="#">P1</a>
GST200	200VA	120	88	115	90	65	3.6	<a href="#">P2</a>
GST250	250VA	120	94	115	90	72	4.0	<a href="#">P2</a>
GST300	300VA	120	100	115	90	78	4.5	<a href="#">P2</a>
GST350	350VA	120	104	115	90	78	4.6	<a href="#">P2</a>
GST400	400VA	135	105	135	115	73	5.5	<a href="#">P2</a>
GST500	500VA	135	110	135	115	78	6.9	<a href="#">P3</a>
GST750	750VA	167	126	155	120	85	10.9	<a href="#">P3</a>
GST1000	1000VA	167	136	155	120	106	14.1	<a href="#">P4</a>
GST1500	1500VA	215	160	200	159	108	20.1	<a href="#">P4</a>
GST2000	2000VA	215	170	200	159	120	25.3	<a href="#">P5</a>
GST2500	2500VA	235	185	225	162	120	28.3	<a href="#">P5</a>
GST3000	3000VA	235	196	225	162	32	32.6	<a href="#">P5</a>

Larger sizes available on request - [contact us](#)